



# MARTIFIN<sup>®</sup> OL-104 LE

## Aluminum Hydroxide

### Einsatzbeispiele / Applications

Flammhemmender Füllstoff, Streichpigment und TiO<sub>2</sub>-Extender für die Papier und Kartonindustrie. Durch Lieferung in weißen Papiersäcken mit wasserlöslicher Klebung und wasserlöslichem Aufdruck ist die direkte Eingabe mit Verpackung in den Pulper möglich.

Flame retardant filler, coating pigment and TiO<sub>2</sub>-extender for the paper and board industry. It is supplied in white paper bags with water soluble adhesives and water soluble markings. Therefore, it can be loaded directly into the pulper with the packaging.

### Durchschnittsanalyse / Typical analysis

Al(OH) <sub>3</sub> -Gehalt / -content	[%]	ca. 99.5
Feuchte / Humidity (105°)	[%]	≤ 0.5
Glühverlust / Loss on Ignition (1200°C)	[%]	34.5
Teilchengröße (Laser Beugung) / Particle Size (laser diffraction)	d <sub>50</sub> [μm]	1.3 – 2.3
	d <sub>90</sub> [μm]	≤ 4.5
Weißgrad / ISO-Brightness (Elrepho 457 nm)	[%]	≥ 95
Teilchenform / Particle shape	plättchenförmig, pseudo-hexagonal platelet, pseudo-hexagonal	
Löslichkeit in Wasser / Solubility in water (20°C, pH 7)	[g/l]	1.5 · 10 <sup>-3</sup>
Brechungsindex / Refractive index		1.58
Spezifische Oberfläche (BET) / Specific surface (BET)	[m <sup>2</sup> /g]	2.5 – 5.5
Dichte / Density	[g/cm <sup>3</sup> ]	2.4
Schüttdichte / Bulk density	[kg/m <sup>3</sup> ]	ca. 350
Härte (nach Mohs) / Hardness (acc. Mohs)		2 – 3

## Shipping Information

Packaging and minimum order quantity information is available from sales or customer service.

## Safety and Handling Information

For specific safety, toxicity and handling information, please refer to the material safety data sheet on this product.

## Chemical Registration Numbers

Chem. Bezeichnung / Chem. name:	Aluminium hydroxide
Formel / formula:	$\text{Al}(\text{OH})_3$
CAS No.:	21645-51-2
EC/EINECS No.:	244-492-7
ENCS:	1-17
ECL:	KE-00980

---

### EUROPE, MIDDLE EAST, AFRICA

Martinswerk GmbH  
Kölner Straße 110  
D-50127 Bergheim

Phone: +49-2271-902-0  
Fax: +49-2271-902-710

### AMERICAS

Huber Engineered Materials  
3100 Cumberland Boulevard  
Suite 600  
Atlanta, Georgia 30339

Phone: +1 (678) 247-7300  
Fax: +1 (678) 247-2797

### ASIA PACIFIC

Huber Fire Retardant Additives  
(Qingdao) Co.Ltd  
8th Floor No.2 Building, No.7,  
Wuyishan Road, Huangdao District,  
Qingdao – China

Phone: +86 532-58792008  
Fax: +86 532-58792008

Web: [www.martinswerk.de](http://www.martinswerk.de)  
[www.hubermaterials.com](http://www.hubermaterials.com)

Email: [info@martinswerk.com](mailto:info@martinswerk.com)  
[hubermaterials@huber.com](mailto:hubermaterials@huber.com)



THERE ARE NO IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Refer to Martinswerk's Standard Conditions of Sale for the only express warranties applicable to the Martinswerk products. Products incorporating Martinswerk products are not warranted by Martinswerk. In no event is Martinswerk liable for consequential damages. **MARTIFIN**® is used, applied for, or registered as a trademark of Martinswerk GmbH in various countries around the world.  
© September 2022 Martinswerk GmbH