

# Vertex<sup>®</sup> 60 SV

## MAGNESIUM HYDROXIDE

### DESCRIPTION

Vertex<sup>®</sup> magnesium hydroxide products provide excellent fire retarding and smoke suppression performance for the thermoplastic and elastomeric compounds. At 330°C, they decompose in an endothermic reaction to form water and magnesium.

Vertex 60 SV is a magnesium hydroxide product surface treated with a proprietary surface treatment that provides superior fire performance when used to make fire-rated polyolefin compounds. The proprietary surface treatment improves compounding rheology and processing as well as compound physical properties.

### GENERAL PHYSICAL AND CHEMICAL PROPERTY DATA

Physical Property	Unit	Typical Value
Specific Gravity	g/cm <sup>3</sup>	2.36
Color		White
Refractive Index		1.58
Hardness	Mohs	2.5
325 Mesh Residue	%	0.3
Median Particle Size by Sedigraph	Microns	1.8
Median Particle Size by Laser Light Scattering	Microns	3.0
Specific Surface Area (BET)	M <sup>2</sup> /g	12

  

Chemical Property	Unit	Typical Value
Magnesium Hydroxide, Mg(OH) <sub>2</sub>	%	≥99 (untreated base)
Calcium	%	≤0.6
Chloride	%	≤0.3
Iron	%	≤0.08
Loss on Ignition (1200°C)	%	≥31 (untreated base)

THERE ARE NO IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. Refer to Huber's Standard Conditions of Sale for the only express warranties applicable to the Huber products. Products incorporating Huber products are not warranted by Huber. In no event is Huber liable for consequential damages.